

Serial No. 10/743,178

Claim 1 (previously presented): A collapsible shade or blind assembly capable of height adjustment, comprising, in combination:

- a) an upper elongated support,
- b) a lower elongated member that is adjustable up and down,
- c) primary lines extending downwardly to suspend said bottom elongated member,
- d) primary rotors or winders to wind or engage said primary lines,
- e) at least one secondary line having operative connection to said primary lines,
- f) and means acting on said secondary line or lines for counterbalancing suspension force exerted on said primary lines at different shade or blind height adjusted levels,
- g) said means including dual rotary members exerting tensioning force on said secondary line or lines,
- h) said means including a spring coupled to said dual rotary members and exerting force tending to entrain said secondary line or lines about said dual rotary members, for storage on at least one of the dual rotary members,

i) said secondary line feeding between said dual rotor members to assist in said spring exertion of force.

Claim 2 (previously presented): The combination of claim 1 wherein the secondary line criss-crosses onto the second member in the form of a drum, for assisting spring exertion of force acting to hold the shade or blind in selected height position.

Claim 3 (previously presented): The combination of claim 1 including rotors entrained by the primary lines, to assist in counterbalancing the weight of the shade.

Claim 4 (previously presented): The combination of claim 1 wherein said winders are pulleys in said upper support.

Claim 5 (previously presented): The combination of claim 1 wherein said dual rotary members are members A and B between which the spring is transferred, and as the spring is transferred from the rotary member A onto rotary member B, the secondary line unwinds from a rotary member and a primary line traverses

Serial No. 10/743,178

across or over first and fourth pulleys and across or over third and second pulleys, then through an aperture in the head rail to suspend the shade or blind, said pulleys defined by said primary winders.

Claim 6 (previously presented): The combination of claim 5 wherein another primary line traverses across or over first and fourth pulleys, and also across or over second and third pulleys, and then passes through an aperture in the head rail to suspend the shade or blind, said primary lines having junction connection to said secondary line.

Claim 7 (previously presented): The combination of claim 1 wherein the shade or blind is raised as one of said rotary members turns counterclockwise and as another of said rotary members turns clockwise, the spring being windingly transferred from one rotary member to the other, one primary line traversing first and fourth pulleys, and then traversing second and third pulleys, to connect with the secondary line.

Serial No. 10/743,178

Claim 8 (original): The combination of claim 7 wherein the other primary line traverses said second and third pulleys and then traverses the first and fourth pulleys to connect with the secondary line, the secondary line winding into secondary line collecting means at said rotary members.

Claim 9 (previously presented): The assembly of claim 8 wherein said first, second, third and fourth pulleys are located in a row at a hollow head rail defined by said upper elongated support, whereby each primary line traverses the pulleys in a back and forth relation.

Claim 10 (original): The assembly of claim 9 wherein said upper elongated support protectively contains all of said pulleys, members and spring.

Claim 11 (original): The assembly of claim 1 wherein said primary lines have first terminals operatively connected to said lower elongated member, below said upper support.

Claim 12 (original): The assembly of claim 1 wherein said support is hollow to receive said rotors, said members, and said spring.

Serial No. 10/743,178

Claim 13 (original): The combination of claim 1 wherein said spring has S-shaped configuration.

Claim 14 (original): The combination of claim 1 wherein said spring winds in a clockwise direction about one of said rotary members, and in a counterclockwise direction about the other of said rotary members.

Claim 15 (original): The combination of claim 1 wherein said at least one rotary member has coaxial first and second surface portions, the spring winding about the first portion, and the secondary line winding about the second portion.

Claim 16 (original): The combination of claim 1 wherein each of the rotary members has coaxial first and second surface portions, the spring winding about the first portions and the secondary line or lines winding about the second portions.

Claim 17 (original): The combination of claim 5 including a housing, and posts in the housing supporting the rotary members for free rotation about axes defined by the posts.

Serial No. 10/743,178

Claim 18 (previously presented): The combination of claim 17 including structure associated with the posts and rotary members, for axially positioning the rotary members in the housing.

Claim 19 (original): The combination of claim 6 wherein the housing is received in said upper elongated support which is a shade or blind head rail.

Claim 20 (previously presented): A collapsible shade or blind assembly capable of height adjustment without use of pull cords, comprising, in combination:

- a) an upper elongated support,
- b) a lower elongated member that is manually adjustable up and down,
- c) primary lines extending downwardly to suspend said bottom elongated member,
- d) primary rotors or winders to entrain said primary lines,
- e) one secondary line having operative connection to said primary lines,
- f) and means acting on said secondary line or lines for counterbalancing suspension force exerted on said primary lines at different shade or blind

Serial No. 10/743,178

height adjusted levels, said means including rotary structure entraining said secondary line, and a spring operatively connected to said rotary structure to coil and uncoil thereabout as shade or blind height changes.

Claim 21 (original): The combination of claim 20 wherein said spring has S-shaped configuration.

Claim 22 (previously presented): The combination of claim 20 wherein said primary winders include four rotors, each primary line entraining at least three of said rotors whereby multiple of said primary lines together entrain at least one rotor.

Claim 23 (previously presented): A collapsible shade assembly capable of height adjustment without use of pull cords, comprising, in combination:

- a) an upper elongated support,
- b) a lower elongated member that is manually adjustable up and down,
- c) primary lines extending downwardly to suspend said bottom elongated member,
- d) primary rotors at said top elongated support to entrain said primary lines,

Serial No. 10/743,178

e) at least one secondary line having operative connection to said primary lines,

f) and means acting on said secondary line or lines for counterbalancing suspension force exerted on said primary lines at different shade height adjusted levels.

Claim 24 (original): The assembly of claim 23 wherein said means includes a rotary member exerting tensioning force on said secondary line or lines.

Claim 25 (original): The assembly of claim 23 wherein the number of said secondary line or lines is less than the number of said primary lines.

Claim 26 (original): The assembly of claim 24 wherein the number of said secondary line or lines is less than the number of said primary lines.

Claim 27 (original): The assembly of claim 23 wherein there is only one secondary line.

Claim 28 (original): The assembly of claim 24 wherein there is only one secondary line, and there are between 2 and 3 of said primary lines.

Serial No. 10/743,178

Claim 29 (original): The assembly of claim 24 wherein said means include a spring or springs acting to urge said rotary member in a direction tending to wind said secondary line or lines on said rotary member.

Claim 30 (original): The assembly of claim 29 wherein said upper elongated support defines a channel in which said primary rotor and said means are located.

Claim 31 (original): The assembly of claim 23 wherein said connection has a linear path of travel.

Claim 32 (original): The assembly of claim 31 wherein said primary rotors are pulleys.

Claim 33 (previously presented): The assembly of claim 31 wherein said primary rotors include a first rotor having spacing from said means which exceeds said path of travel for shade height adjustment between selected upper and lower positions.

Claim 34 (original): The assembly of claim 33 wherein said primary rotors include at least one second rotor over which said primary lines are entrained, and said primary rotors include a third rotor in the form of a

Serial No. 10/743,178

pulley over which one of said primary lines is entrained, and a fourth rotor in the form of a pulley over which another of said primary lines is entrained.

Claim 35 (original): The assembly of claim 34 wherein said upper elongated support protectively contains all of said primary rotors and said tensioning means.

Claim 36 (original): The assembly of claim 23 wherein said primary lines have first terminals operatively connected to said lower elongated member, below said upper support.

Claim 37 (original): The assembly of claim 36 wherein said primary lines have second terminals operatively connected to said connection, within said upper support.

Claim 38 (original): The assembly of claim 31 including a guide rotor over which a section of said secondary line travels, said section located between said connection and said means, said guide rotor movable axially generally normal to said path of travel.

Serial No. 10/743,178

Claim 39 (original): The assembly of claim 23 wherein said means includes a roller device for retaining said secondary line in a selected position or positions corresponding to selected shade height adjustment.

Claim 40 (previously presented): For use in operation of a collapsible shade or blind assembly capable of height adjustment, the combination comprising:

- a) an upper elongated support,
- b) a lower elongated member that is manually adjustable up and down,
- c) primary lines extending downwardly to suspend said bottom elongated member,
- d) pulleys at said top elongated support to entrain and wind or engage said primary lines,
- e) at least one secondary line having operative connection to said primary lines,
- f) one primary line traversing across or over first and fourth pulleys and across or over third and second pulleys, then downwardly to suspend the shade or blind.

Serial No. 10/743,178

Claim 41 (previously presented): The combination of claim 40 wherein another primary line traverses across or over first and fourth pulleys, and also across or over second and third pulleys, and then passes downwardly to suspend the shade or blind, said primary lines having junction connection to said secondary line.

Claim 42 (previously presented): The combination of claim 40 wherein the shade or blind is raised as one rotary member turns counterclockwise and as another rotary member turns clockwise, and a spring which is windingly transferred from one rotary member to the other.

Claim 43 (previously presented): The combination of claim 42 wherein the other primary line traverses said second and third pulleys and then traverses the first and fourth pulleys to connect with the secondary line, the secondary line winding into secondary line collecting means at said rotary members.

Serial No. 10/743,178

Claim 44 (previously presented): The assembly of claim 43 wherein said first, second, third and fourth pulleys are located in a row, whereby each primary line traverses the pulleys in a back and forth relation.

Claim 45 (previously presented): The assembly of claim 41 wherein an upper elongated support is provided to protectively contain all of said pulleys, and a spring tensioning said secondary line.

Claim 46 (previously presented): The combination of claim 45 wherein said spring has S-shaped configuration, to wind about spring transfer members.

Claim 47 (new): A collapsible shade or blind assembly capable of height adjustment without use of pull cords, comprising, in combination:

- a) an upper elongated support,
- b) a lower elongated member that is manually adjustable up and down,
- c) primary lines extending downwardly to suspend said bottom elongated member,
- d) primary rotors to entrain said primary lines,

Serial No. 10/743,178

e) there being one secondary line having operative connection to said primary lines,

f) including a rotary member entraining said secondary line, and a spring operatively connected to said rotary member to variably coil thereabout as shade or blind height changes, whereby said rotary member exerts counterbalancing suspension force exerted on said primary lines at different shade or blind height adjusted levels.

Claim 48 (new): The combination of claim 47 including an additional rotary member to which said spring is also operatively connected.

Claim 49 (new): The combination of claim 48 wherein said spring coils about said additional rotary member.